





# UHD Intelligent 4K Bullet IP Camera

## Features

- Sony 1/2.5" 8MP CMOS sensor
- H.265 / H.264 / M-JPEG dual streams
- Built-in video analytic functions
- Motorized vari-focal lens
- Region of interest (ROI)
- Automatic network replenishment (ANR)
- Micro SD slot for recording
- Day/Night (ICR), T-WDR (120dB), 3DNR, AGC, defogging
- ONVIF (Profile S)
- Power over Ethernet (PoE)



## Dimensions



## Specifications

Model	NM8-B36W
<b>CAMERA</b>	
Image Sensor	Sony 1/2.5" 8MP CMOS sensor
Effective Pixel	3840 (H) x 2160 (V)
Frame Rate	25/30fps
Resolution	Up to 3840 x 2160@15fps (main stream); Up to D1@25/30fps (sub stream);
Video Compression	H.265 / H.264 / M-JPEG (16kbps -16Mbps)
Audio Compression	G.711u (64kbps)
Open Standard	ONVIF (Profile S)
Min. Illumination	0.0 lux (IR on)
IR Range	40m
Sync System	Internal
Scan System	Progressive scan
Lens	3.0-10mm motorized lens
Angle of View	Horizontal: 41° ~ 97°; Vertical: 21° ~ 53°
Electronic Shutter	Auto / manual (1/30-1/10000) / FLK
<b>CONTROL</b>	
Video Adjustment	Brightness, contrast, saturation, sharpness, hue
3D Noise Reduction	Close / low / mid / mid-high / high
True WDR	Close / low / mid / high
Auto Gain Control	Low / mid-low / mid / mid-high / high
Day / Night	Auto / color / B/W / external
Privacy Mask	4 zones
ROI	4 zones
Mirror	Close / horizontal / vertical / 90° rotation / 180° rotation / 270° rotation
Defogging	Close / low / mid / high
Slow Shutter	Close / open
<b>EVENT</b>	
Event Type	External alarm, video motion detection, video tamper, network interruption
Video Analysis	Tripwire, loitering, missing / unattended object detection, crowd monitoring
Action Type	Dial-back, snapshot, relay switch control, email notification, micro SD card recording
External Alarm Input	2
Motion Detection	4
Relay Output	1
<b>COMMUNICATION</b>	
Network	RJ-45, 100 base-T
Protocol	TCP/IP, UDP, HTTP, DHCP, RTSP, DDNS, SMTP(SSL), PPPoE, UPNP, NTP, P2P, FTP
Concurrent Connection	4
Audio Input	1
Audio Output	1
Video Output	1 (CVBS)
<b>MISCELLANEOUS</b>	
Weather Protection	IP66
Operating Environment	-20 ~ 55°C / 90% relative humidity (no condensation)
Power Supply	DC12V / PoE, 9W
Dimensions (mm)	93 (W) x 96 (H) x 263 (L)
Weight	904g

