



## 8CH 5MP H.264 NVR

### Features

- 8-channel real time recording up to 5MP
- H.264 dual-stream recording
- Sophisticated event management
- Synchronized 8-ch playback
- 12x video magnification
- DDNS, P2P for Internet connectivity
- Embedded Linux ensuring reliable operations



### Dimensions



### Specifications

Model	NW-12008
<b>VIDEO</b>	
Compatibility	WAMA & ONVIF (Profile S) IP cameras
Input	8
Resolution	2592x1944, 2048x1536, 1920x1080, 1280x960, 1280x720, 960x576
Output	VGA, HDMI, 1080p@60Hz
Compression	H.264
Bit Rate	16-8000kbps
Display	1/4/6/8/9
<b>AUDIO</b>	
Input	IPC audio in
Output	-
Compression	G.711A
<b>RECORDING AND PLAYBACK</b>	
Max. Frame Rate	25/30fps
HDD	2 x 3.5" SATA
Recording Mode	Manual, event driven, schedule
Simultaneous Playback	8 channels
Searching Mode	Advanced timeline, channel, event, past moment
Playback Mode	Normal, fast FWD/BWD, slow FWD/BWD, 30-sec step, frame-by-frame
Snapshot	JPEG format
Back-up	Network, USB
<b>EVENT</b>	
Event Type	External alarm, video motion detection, video analytic (with intelligent IP cameras)
Video Analytic Function	-
Video Analytic Channel	-
Action Type	Dial-back, relay switch control, email notification, buzzer
External Alarm Input	2 + IPC alarm in
Relay Output	1
<b>COMMUNICATION</b>	
Network	RJ-45, 100 base-T
Protocol	TCP/IP, HTTP, DDNS, SMTP (SSL), DHCP, PPPoE, UPNP, NTP, P2P, FTP
Concurrent Connection	4
<b>MISCELLANEOUS</b>	
Operating Environment	-10°C ~ 55°C / 90% relative humidity (no condensation)
Power Supply	DC12V/4A, 10W (excluding HDD)
Dimension (mm)	360 (W) x 242 (D) x 48 (H)
Weight	2 kg (excluding HDD)

Design and specifications are subject to change without prior notice.  
 Copyright © 2017 WAMA Technology Limited.  
 Version no. 1712A



**AVAS USA**  
 7421 Douglas Blvd Suite N #217  
 Douglasville, GA 30135.  
 Tel : 770-941-2827  
 Fax : 770-941-2827

Email : [info@avasusa.com](mailto:info@avasusa.com)  
 Website : [www.avasusa.com](http://www.avasusa.com)